



YONGCHENG

SPECIFICATION FOR APPROVAL

DATE: AUG 18, 2008

SAMPLE Q'TY 12 PCS

CUSTOMER : ACUWA

CUSTOMER P/N: AF-009A-1

YONGCHENG P/N : YH-16D01A

DESCRIPTION : 10/100 BASE-TX TRANSFORMER

APPROVED SIGNATURES	
YONGCHENG APPROVED SIGNATURES	CUSTOMER APPROVED SIGNATURES
APPROVED BY: LiaoZongCheng	APPROVED BY:
DATE: 2007/8/18	DATE:
APPROVED No. :	APPROVED No. :

(ZUNYI)YONGCHENG ENTERPRISE INC.

LanGongShan,ZunYi City,GuiZhou,China

Tel: 0852-3162322 13087896733 Fax: 0852-3162322 E-mail<lzc0818@163.com>

SAMPLES TEST REPORT



Page :2/3

PART NO.		AF-009A		DATE			2008/8/18					
DESCRIPTION		10/100BASE-TX TRANSFORMER										
ITEM	TEST EQUIPMENTS	TEST CONDITION @ 25℃	SAMPLES NO. TEST PIN	1	2	3	4	5	SPECIFICATION			
			Min						Typ	Max		
OCL (uH MIN)	3250	100KHz/0.1V with 8mA DC BIAS	1-2	478	483	512	526	487	350			
			10-11	485	493	488	498	516				
HI-POT(Vrms)	GPI-5005T	1500Vrms	PRI/SEC	PASS	PASS	PASS	PASS	PASS	1S			
Cross Talk (dB MIN)	8711/8712	0.1-60 MHz	TX OR RX	-49.6	-46.7	-47.5	-47.2	-48.3	-40			
		60-100 MHz	TX OR RX	-41.6	-39.5	-40.5	-41.8	-41.3				-38
TURN RATIO	CA8120A	1MHz/sine wave	1-2:7-6	1.001	0.999	0.999	1.000	1.001	1CT:1CT			
			10-11:16-15	0.999	1.000	1.000	0.999	0.999				
Insertion Loss (dB MAX)	8711/8712	0.1-125 MHz	TX	-0.51	-0.38	-0.49	-0.42	-0.45	-1.1			
			RX	-0.55	-0.36	-0.47	-0.47	-0.52				
Return Loss(dB MIN)	8711/8712	0.1-60 MHz	TX	-23.9	-24.8	-24.3	-25.2	-25.6	-18			
			RX	-24.2	-25.5	-24.8	-23.6	-25.1	-17			
		60-100 MHz	TX	-18.8	-16.9	-17.2	-18.3	-17.6	-13			
			RX	-18.6	-17.3	-18.5	-17.4	-17.9	-15			
CMRR (dB MIN)	8711/8712	0.1-60 MHz	TX	-54.8	-52.7	-53.2	-54.6	-53.9	-42			
			RX	-54.7	-50.9	-52.4	-53.6	-53.1	-40			
		60-100 MHz	TX	-44.2	-43.1	-44.6	-43.8	-45.1	-40			
			RX	-44.5	-42.6	-43.9	-45.5	-42.1	-35			