


1. DCR :
PIN 1-3 = 445 OHM MAX.
PIN 4-6 = 34 OHM MAX.
2. INDUCTANCE (@1KHZ , 1Vrms) :
PIN 1-3 = 12 H MIN.
3. IMPEDANCE (@15KHZ , 1Vrms , PIN 4-6 W/H 2 KOHM) :
PIN 1-3 = 32 KOHM $\pm$ 5%.
4. INSERTION LOSS (@15KHZ, 1Vrms , PIN 4-6 W/H 2 KOHM) = 1 dB MAX.
5. FREQ RESP. (@REF 15KHZ) :
1KHZ = $\pm$ 0.5dB.
35KHZ = $\pm$ 0.5dB.
6. TURN RATIO (@13KHZ , 1Vrms)
PIN 1-3 : 6-4 = 4 ± 1 %.
7. HI-POT (@3750VAC , 1mA , 1MIN) : PIN 1-4.

						 Atech Technology Co., Ltd. TEL: 0272784-0007 FAX: 0272784-0004	TITLE TRANSFORMER	
							DWG. NO. ATC-03-057	
	RELEASE	12/29/2003	BART	YEN	SUEDY	UNITS: M/M	SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE 12/29/03	SHEET 10f 1 DRAW <i>Pair</i>	
REVISIONS								