



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 7.5 Ω HM MAX.
PIN 3-4 = 7.5 Ω HM MAX.
PIN 5-6 = 0.8 Ω HM MAX.
PIN 7-8 = 0.8 Ω HM MAX.
- INDUCTANCE (@1KHZ, 0.3Vrms) :
PIN 1-2 = 5.6 mH $\pm$ 20%.
PIN 3-4 = 5.6 mH $\pm$ 20%.
PIN 5-6 = 1.4 mH $\pm$ 20%.
PIN 7-8 = 1.4 mH $\pm$ 20%.
- TURN RATIO (@1KHZ, 0.1Vrms) :
PIN 4-1:8-5 (2-3, 6-7 SHORT) = 2 $\pm$ 1%.
- HI-POT (@500VAC, 1mA, 1MIN) :
PRI-SEC, PRI-CORE, SEC-CORE.

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE TRANSFORMER	
								DWG. NO. ATC-04-063	
	RELEASE	10/01/2004	BART	MICHAEL	SUEDY	UNITS: M/M	SAFETY	SHEET 10F 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>	
REVISIONS						10/01/04			