




ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 370 mΩ MAX.
PIN 3-4 = 250 mΩ MAX.
PIN 7-9 = 30 mΩ MAX.
PIN 8-10 = 30 mΩ MAX.
- INDUCTANCE (@10KHz, 0.1Vrms) :
PIN 3-4 : 147uH ±5%.
- LEAKAGE INDUCTANCE (@100KHz, 0.1Vrms) :
PIN 1-3 (2-4, 7-8-9-10 SHORT) = 3.4uH MAX.
- TURN RATIO (@2MHz, 0.1Vrms) :
PIN 3-4:2-1 = 2.06 ±6%.
PIN 3-4:8-9 = 2.06 ±6%.
- HI-POT :
(@1.5KV, 1mA, 2S) :
PIN 1-10 (2-3,7-8 SHORT)
PIN 1-CORE (2-4-7-10 SHORT)
PIN 1-4
(@0.5KV, 1mA, 2S) :
PIN 7-10

						Atech® Atech Technology Co., Ltd. TEL: 82794-6667 FAX: 82794-8884		TITLE		ADSL TRANSFORMER
								DWG. NO.		ATC-05-025
	RELEASE	05/23/2005	BART	FRANK	SUEDY	UNITS:	SAFETY		SHEET 1 of 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	M/M			DRAW	
REVISIONS						DATE	05/23/05			