



ELECTRICAL CHARACTERISTICS :

1. PRIMARY RATED VOLTAGE AND FREQUENCY : 25V 60Hz.
2. EXCITING CURRENT: INPUT PRIMARY 25V 60Hz.
3. SECONDARY RATED VOLTAGE :

INPUT VOLTAGE	COLOR/PIN NO.	RATED VOLTAGE	RATED CURRENT	NOLOAD VOLTAGE
25V/60Hz	1-2	AC10V \pm 5%	1.6 A	AC11.7V \pm 5%

4. HI-POT TEST : SHALL WITHSTAND WITHOUT BREAKDOWN :
(INPUT 60Hz LEAKAGE CURRENT 5 mA/1MIN.)
1.0 KV FOR ONE MINUTE BETWEEN PRIMARY TO SECONDARY.
1.0 KV FOR ONE MINUTE BETWEEN PRIMARY TO CORE.
1.0 KV FOR ONE MINUTE BETWEEN SECONDARY TO CORE.
5. INSULATION TEST : 500VDC 100M OHM MIN.
BETWEEN WINDINGS AND WINDINGS AND CORE.
6. RoHS COMPLIANCE.

						Atech® Atech Technology Co., Ltd. TEL: 02-2704-8887 FAX: 02-2704-8004	TITLE POWER TRANSFORMER	
							DWG. NO. ATC-05-035R	
	RELEASE	09/20/2005	BART	AL	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE		
REVISIONS						09/20/05	DRAW	Pair