








ELECTRICAL CHARACTERISTICS :

- D.C.R. : PIN 2-1 = 34 mΩ MAX.
PIN 3-1 = 65 mΩ MAX.
PIN 5-7 = 1265 mΩ MAX.
PIN 10-8 = 3764 mΩ MAX.
- INDUCTANCE (@10KHz, 0.1Vrms, ALC OFF) :
PIN 10-8 = 2.5mH±6%
- LEAKAGE INDUCTANCE:
PIN 10-8 (7-5,1-2-3 SHORT) = 102 uH MAX.
- INTERWINDING CAP (@100KHz, 0.1Vrms) :
PIN 1-5 = 15 pF MAX. PIN 1-10 = 15pF MAX.
- TURN RATIO (@200KHz, 0.1Vrms) :
PIN 10-8 : 2-1 = 40.67±2%
PIN 10-8 : 3-2 = 17.43 ±2%
PIN 10-8 : 5-7 = 4.52±2%
- HI-POT (@500VAC, 1mA, 2SEC) :
PRI-SEC .
- RoHS COMPLIANT

						Atech®		TITLE TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATC-06-022R	
						TEL:0212794-6667 FAX:0212794-8004			
RELEASE		05/15/2006	PAIR	LYS	EUGENE	UNITS: M/M		SAFETY	
DESCRIPTION		DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1	
REVISIONS						05/15/06		DRAW Pair	