

ELECTRICAL TEST REPORT

CUSTOMER : 國 驚 (ATC-1896)
 PART NUMBER : ~~ATC 94-029~~
 REV OR EC NUMBER :

DATE TESTED : 07/13/94
 TESTED BY :

SPEC.\SAMPLE NO.	1	2	3	4	5
DCR :OHM 1-2 = 0.85 MAX	0.75	0.75	0.75	0.74	0.75
4-5 = 0.70 MAX	0.62	0.62	0.62	0.62	0.62
6-7 = 7.8 MAX	7.03	6.98	6.97	6.98	6.97
9-10 = 7.8 MAX	7.06	7.08	7.02	7.02	7.08
INDUCTANCE (@1KHZ,0dBm) 1-2(W/O DC)=3mH MAX	2.23	2.54	2.52	2.82	2.43
1-2(W/H 80mADC) =2mH MIN	2.20	2.36	2.34	2.59	2.23
INTERWINDING CAP. (@1KHZ,0dBm) 1-4 =250PF MIN	353	291	329	328	358
1-6 = 400PF MIN	532	480	495	552	541
4-6 = 350PF MIN	589	413	498	458	529
6-9 = 480PF MIN	758	623	648	658	749
TURNS RATIO (@10KHZ,0dBm,W/H 2-4,7-9 SHORT) 6-10:5-1 = 2 +/-1%	2.013	2.013	2.014	2.013	2.013
HI-POT(@200VAC,1mA, 1 MINUTE) 1-4,1-6,1-9 4-6,4-9,6-9	OK	OK	OK	OK	OK