



ELECTRICAL CHARACTERISTICS :

1. MEET ANNEX E OF ITU-T REC.G.992.1
2. DCR EACH LINE : 10 OHM MAX.
3. INSERTION LOSS (@1KHZ) : 0.3 dB MAX.
4. INSERTION LOSS RESPONSE (@300-3.4KHZ) : ± 0.3 dB
5. ATTENUATION (@30K-300KHZ) : 65 dB MIN.
(@300KHZ-1.04MHZ) : 55 dB MIN.
6. RETURN LOSS : (@200HZ) = 14 dB MIN.
(@500HZ) = 18 dB MIN.
(@2KHZ) = 18 dB MIN.
(@3.4KHZ) = 14 dB MIN.
7. LONGITUDINAL BALANCE (@200~4KHZ) : 53 dB MIN.
8. COMMON MODE REJECTION (@40KHZ) : 55 dB MIN.
(@1.1MHZ) : 25 dB MIN.
9. DELAY DISTORTION (@200~4KHZ) : 150 μ SEC MAX.
10. POTS LOOP CURRENTS : 120 mA
11. POTS TIP TO RING DC VOLTAGE 0-200V
12. POTS RINGING SIGNAL FROM 15.3HZ TO 68HZ : 150 Vrms

						Atech® Atech Technology Co., Ltd. TEL(02)2794-6667 FAX(02)2794-8004		TITLE POST SPLITTER	
								DWG. NO. ATF028AC	
RELEASE		07/15/2003	RDRY	SIMON	SUEDY	UNITS: M/M		SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE			
REVISIONS						07/15/03		SHEET 1 OF 1	
								DRAW <i>Pair</i>	