


ELECTRICAL CHARACTERISTICS : MEET ITU-T G.992.1

1. FOR COMPLEX IMPEDANCE : 320 OHM + (1050 OHM // 230nF)
2. DCR EACH LINE : 25 OHM MAX.
3. INSERTION LOSS (@1KHZ) : 1dB MAX.
4. INSERTION LOSS DISTORTION (@200HZ-4KHZ) : ± 1dB
5. FREQ. PULSE METERING INSERTION LOSS (@12/16KHZ) : 3dB MAX.
6. RETURN LOSS (@300HZ-500HZ) : 14dB MIN.
 (@500HZ-2KHZ) : 18dB MIN.
 (@2KHZ-3.4KHZ) : 14dB MIN.
7. LONGITUDINAL BALANCE (@15HZ-50HZ) : 40dB MIN.
 (@50HZ-600HZ) : 46dB MIN.
 (@600HZ-3.4KHZ) : 52dB MIN.
8. DELAY DISTORTION (@200HZ-4KHZ) : 200uSEC MAX.
9. ATTENUATION (@32KHZ-1.1MHZ) : 55dB MIN.
10. ISOLATION (@T-R) : 1M OHM MIN.
 (@T-G, R-G) : 10M OHM MIN.
11. LOOP CURRENT : 100mA

					Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004	TITLE ADSL POTS SPLITTER		
						DWG. NO.	ATF041	
A	ADD FUSE	02/04/2002	DOLLY	JEFF		SUEDY		
	RELEASE	11/21/2001	PAIR	JEFF	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE		
REVISIONS						11/21/01		