

ATM-021 ELECTRICAL CHARACTERISTICS

MAXIMUM RATINGS

Supply Voltage	+35V / +5.25V
Inhibit, F1 and F0 Input Voltage	-0.5V to+5.2V
Operating Ambient Temperature (TA)	-40°C to+85°C
Storage Temperature	-40°C to+100°C
Lead Temperature (Soldering, 10 sec max.)	+300°C

FUNCTIONAL SPECIFICATIONS

Typical at: TA=+25°C, Vin=+24.0Vdc, Load=1400Ω resistive, Cin=330μF, OAC not connected.

Parameters	Conditions	Min	Typ	Max	Units
Supply (+24Vin)					
Supply Voltage	100-120Hz, $19.2 \leq V_{in} \leq 30.0V_{dc}$	19.2	24.0	30.0	Vdc
Supply Voltage Ripple				1.5	Vp-p
Current Consumption				24	mA
Average Current			85	370	mA
Peak Current	Device Inhibited No Load Load=1400Ω, @ Vin=19.2Vdc Load=1400Ω, @ Vin=19.2Vdc			700	mA
Suppply (+5Vin)					
Supply Voltage	@Continuous @Surge of 200nsec every 3μsec	4.75	5.00	5.25	Vdc
Input Current				35 110	mA mA
Efficiency		64	72		%
Output					
Power	Continuous Loading	0		5	VA
Power Factor		0.7			[cos ϕ]
Output Voltage	OAC not connected , Pout=3VA	70	75	82	Vrms
Output Frequency	According to F0,F1 setting (Refer to Page 1)		16.7, 20, 25,50		Hz
Frequency Accuracy	$19.2 \leq V_{in} \leq 30.0V_{dc}$, $0 \leq P_{out} \leq 4VA$, $-40^{\circ}C \leq T_A \leq +85^{\circ}C$ $19.2 \leq V_{in} \leq 30.0V_{dc}$, $0 \leq P_{out} \leq 4VA$, $-40^{\circ}C \leq T_A \leq +85^{\circ}C$			±3	%
THD				5	%
Inhibit Control Input					
Disable Voltage VIH	VIL = 0V VIH = 5V	3.5	5	5.2	Vdc
Enable Voltage VIL		-0.5	0	1.0	Vdc
Iin Source				50	μA
Iin Sink				700	μA
F0,F1 Control Input *					
VIH	VIL = 0V	3.5		5.2	Vdc
VIL		-0.5		1.0	Vdc
Iin Source				700	μA
Timing					
Inhibit Response	Output Overloaded Load reverts to Normal; $0 \leq P_{out} \leq 4VA$	30		50	ms
Time to Turn-On				35	ms
Time to Turn-Off		200	600 5	800	ms
Overload Protection Response					s
Time to Turn-Off					
Time to Turn-On					
General					
Insulation	500Vdc Input to Output	40	94		MΩ
Switching Frequency					kHz
Environment					
Ambient Temperature (TA)	From +50°C output derated by 0.1W/°C	-40 -40		+50	°C
Without Derating				+85	°C
With Derating					
Sync Output Timing					
SYNC Pulse Width	Output Frequency=16.7, 20, 25 Hz Output Frequency=50 Hz	4.5		5.5	ms
		3.6		4.4	ms
OHD Output Timing					
Off-Hook Response Time	Output Overloaded			40	ms
OHD,Sync Output					
VoH	Referenced to GND Terminal Output Source Current 2mA	4.2		5.3	Vdc
VoL	Output Sink Current 2mA	0		0.8	Vdc
VoL	Output Sink Current 5mA	0		1.2	Vdc

* DO NOT CHANGE THE FREQUENCY SETUP WHILE THE RING GENERATOR OUTPUT IS ENABLED.