



ELECTRICAL CHARACTERISTICS :

- INPUT :
 RATED VOLTAGE : 100 ~ 240VAC
 MAX. VOLTAGE : 90 ~ 264VAC
 LINE FREQUENCY : 47~ 63Hz
 CURRENT : 1200mA, @ 100-240VAC
 CONFIGURATION : IEC-320, C8, 2PIN
- OUTPUT :
 VOLTAGE : 24VDC
 CURRENT : 2.1A
 WATT : 50.4W
 EFFICIENCY : 78%
 RIPPLE VOLTAGE : 240mVp-p MAX.
 OPERATING TEMP. : 0°C ~ 40°C
 STORAGE TEMP. : -20°C ~ 80°C
 OPERATING HUMIDIFY : 20% ~ 80%
- SAFETY : UL,CUL,TUL,TUV/GS,CB,CE,PSE,CCC,LPS
- TOPOLOGY : SWITCHING MODE
- HI-PDT : (<@3000 V,1SEC.5mA) PRI-SEC
- LEAKAGE CURRENT : (<@240VAC/50Hz)≤0.25mA
- RoHS COMPLIANT

						Atech®		TITLE SWITCHING POWER SUPPLY	
						Atech Technology Co. Ltd.		DWG. NO.	
						TEL:02)2794-6667 FAX:02)2794-8004		ATPS-045R	
RELEASE		04/10/2007	PAIR	WILLIE	EUGENE	UNITS: M/M		SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1	
REVISIONS						04/10/07		DRAW Pair	