




BLACK DOT PIN#1

Atech
ATS-247



ELECTRICAL CHARACTERISTICS: (FOR 56Kbps)

1. D.C.R. : PIN 1-3 = 108 OHM+/-10% PIN 6-4 = 120 OHM+/-10%
2. INDUCTANCE (@200HZ, 1Vrms, PARALLEL) : PIN 1-3 = 25H MIN.(40H TYP.)
3. RETURN LOSS : (REF. 600 OHM) 300 TO 3.5KHZ = 15dB MIN.
4. INSERTION LOSS : (1KHZ, 0dBm) 2.25dB MAX.
5. FREQ. RESPONSE: (REF. 1KHZ) 200 TO 4KHZ = +/-0.2dB
6. LONGITUDINAL BALANCE : 200HZ-4KHZ 70dB MIN.
7. TURN RATIO : (6KHZ, 1Vrms) PIN 1-3 : 6-4 = 1+/-1%
8. DISTORTION : 300HZ, -10dBm : -83dB MAX.
150HZ, -3dBm : -75dB MAX.
9. HI-POT : (@1250VAC, 1mA, 2SEC.) PIN 1-6

						Atech® Atech Technology Co., Ltd. TEL:(02)2794-8867 FAX:(02)2794-8004		TITLE 600 : 374 TRANSFORMER	
								DWG. NO. ATS-247BE	
	RELEASE	10/01/2004	BART	SUEDY	SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE 10/01/04	E159603 		DRAW <i>Pair</i>
REVISIONS									