



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 120 OHM $\pm 10\%$.
PIN 4-6 = 120 OHM $\pm 10\%$.
- INDUCTANCE (@200Hz, 1Vrms, PARALLEL) :
PIN 1-3 = 2.86 H MIN.
- RETURN LOSS (@-10 dBm, REF. 600 OHM) :
200Hz = 20 dB MIN.
3.5KHz = 20 dB MIN.
- INSERTION LOSS (@0 dBm, PIN 4-6 W/H 360 OHM) :
1KHz = 2.1 dB TYP.
- FREQ. RESPONSE (@REF. 1KHz) :
100Hz = ± 0.5 dB.
4KHz = ± 0.5 dB.
- TURN RATIO (@1KHz, 1Vrms) :
PIN 1-3:4-6 = 1 $\pm 1\%$.
- HI-POT (@1650VAC, 1mA, 2SEC) :
PIN 1-6

						Atech® Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004		TITLE	
								TRANSFORMER	
								DWG. NO.	
								ATS-273BC	
	RELEASE	09/06/2005	BART	LYS	SUEDY	UNITS:		SAFETY	
						M/M			
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1	
REVISIONS						09/06/05		DRAW	
								Pair	