


ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN 1-3 = 150 OHM $\pm$ 12% PIN 6-4 = 150 OHM $\pm$ 12%
2. INDUCTANCE (@250HZ, 1Vrms, PARALLEL) : PIN 1-3 = 18H MIN.
3. RETURN LOSS : (REF. 600 OHM) 200 TO 4KHZ = 30dB MIN.
4. INSERTION LOSS : (@1KHZ, 0dBm) PIN 1-3 = 3 $\pm$ 0.3 dB
5. FREQ. RESPONSE : (REF. 1KHZ) 200 TO 4KHZ = $\pm$ 0.2 dB
6. LONGITUDINAL BALANCE : 200 HZ - 4KHZ 80 dB MIN.
7. TURN RATIO : (@9KHZ, 1Vrms) PIN 1-3 : 6-4 = 1 $\pm$ 1%
8. HI-POT : (@1250VAC, 1mA, 2SEC) PRI-SEC
9. LEAD-FREE

					Atech®		TITLE 600 : 301 TRANSFORMER	
					Atech Technology Co., Ltd.		DWG. NO. ATS-354BCN	
					TEL:(02)2794-8867 FAX:(02)2794-8004			
RELEASE	03/01/2004	DOLLY	PAIR	SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO. DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW Pair
REVISIONS					03/01/04			