



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN 1-3 = 6-4 = 113 OHM $\pm$ 12%
2. INDUCTANCE (@250HZ, 1Vrms, PARALLEL) : PIN 1-3 = 14H MIN.
3. RETURN LOSS : (REF. 600 OHM) 200 TO 4KHZ = 30dB MIN.
4. INSERTION LOSS : (@1KHZ, 0dBm) PIN 1-3 = 2.1 $\pm$ 0.3 dB
5. FREQ. RESPONSE : (REF. 1KHZ) 200 TO 4KHZ = $\pm$ 0.2 dB
6. LONGITUDINAL BALANCE : 200 HZ - 4KHZ 80 dB MIN.
7. TURN RATIO : (11KHZ, 1Vrms) PIN 1-3 : 6-4 = 1 $\pm$ 1%
8. HI-POT : (@1500V, 5mA, 2SEC) PRI-SEC
9. RoHS COMPLIANCE.



						Atech® Atech Technology Co.. Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004		TITLE 600: 374 TRANSFORMER	
								DWG. NO. ATS-369AR1	
	RELEASE	03/22/2007	PAIR	WILLIE	EUGENE	UNITS: M/M	SAFETY		
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE 03/22/07			
REVISIONS								SHEET 1 OF 1	
								DRAW <i>Pair</i>	