








ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 2-4 = 0.4 OHM $\pm$ 12%
PIN 8-6 = 7-5 = 0.47 OHM $\pm$ 12%
- INDUCTANCE (@10KHZ, 0.1Vrms) : PIN 8-5 (6-7 SHORT) = 474uH $\pm$ 5%
- LEAKAGE INDUCTANCE (@10KHZ, 0.1Vrms) :
PIN 8-5 (6-7 1-4 2-3 SHORT) = 15uH MAX.
- INTERWINDING CAP. (@10KHZ, 0.1Vrms) :
PIN 1-8 (6-7 2-3 SHORT) = 30pF MAX.
- TURN RATIO (@730KHZ, 1Vrms) :
PIN 8-5 (7-6 SHORT) : 1-4 (2-3 SHORT) = 1.417 $\pm$ 2%
- HI-POT (@1875VAC, 1mA, 1SEC) : PRI-SEC

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE ADSL TRANSFORMER	
								DWG. NO. ATS-559	
	RELEASE	12/06/2001	DOLLY	JEFF	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>	
REVISIONS						12/06/01			