



1. DCR : PIN 1-5 = 2-4 = 1.88 OHM MAX.
PIN 5-3 = 2-6 = 2.35 OHM MAX.
2. INDUCTANCE (@10KHZ, 0.1Vrms) :
PIN 1-3 = 35 mH MIN.
3. CAPACITOR (@10KHZ, 0.1Vrms) :
PIN 1-4 = 1.85 nF TYP.
4. RETURN LOSS :
(@300HZ, 0.1Vrms) : 25 dB MIN.
(@100KHZ, 0.1Vrms) : 25 dB MIN.
(@500KHZ, 0.1Vrms) : 20 dB MIN.
6. Z (@10KHZ, 0.1Vrms, 4-6 W/H 100 OHM) :
PIN 1-3 = 100 OHM TYP.
7. HI-POT (@500VAC, 1mA, 2S) : PIN 1-4.
8. LEAD FREE.

						 Atech [®] Atech Technology Co., Ltd. TEL: (02) 2794-6667 FAX: (02) 2794-8004	TITLE TRANSFORMER	
							DWG. NO. ATS-726AR	
	RELEASE	07/09/2007	PAIR	MICHAEL	EUGENE	UNITS: M/M	SAFETY	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	SHEET 1 OF 1 <i>Pair</i>
REVISIONS						07/09/07		