




ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-4= 2-5= 500 mOHM MAX
PIN 9-6 = 10-7 = 257 mOHM MAX.
- INDUCTANCE (@10KHz, 0.1Vrms) :
PIN 1-5 (2-4 SHORT) = 410 uH ±5%.
- LEAKAGE INDUCTANCE (@300KHz, 0.1Vrms) :
PIN 1-5 (2-4,6-7-9-10 SHROT) = 8.6 uH MAX.
- INTERWINDIG CAP(@100KHz, 0.1Vrms) :
PIN 1-10 (2-4, 7-9 SHROT) = 37 pF MAX.
- TURN RATIO (@1MHz, 0.1Vrms) :
PIN 1-5 (2-4 SHROT) : 10-6 (9-7 SHROT) = 2 ±2%.
- HI-POT (@1875VAC, 1mA, 2S) :
PRI-SEC

						Atech® Atech Technology Co., Ltd. TEL:02)2794-6667 FAX:02)2794-8004	TITLE ADSL TRANSFORMER	
							DWG. NO. ATS-750A	
A	DELTED MFG. MARK	01/18/2007	PAIR	WILLIE	EUGENE	UNITS: M/M	SAFETY	SHEET 1 OF 1
	RELEASE	07/28/2005	BART	EEFLYS	SUEDY			
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW	
REVISIONS						07/28/05	Pair	