





ELECTRICAL CHARACTERISTICS : MEET ITU-T G.992.1

1. FOR COMPLEX IMPEDANCE : 270 OHM + (750OHM // 150nF)
2. DCR EACH LINE : 25 OHM MAX.
3. INSERTION LOSS (@1KHZ) : 1dB MAX.
4. INSERTION LOSS DISTORTION (@200HZ-4KHZ) : ± 1dB
5. FREQ. PULSE METERING INSERTION LOSS (@12/16KHZ) : 3dB MAX.
6. RETURN LOSS LINE&PHONE PORT (@300HZ-3.4KHZ) : 14dB MIN.
(@3.4KHZ-4KHZ) : 12dB MIN.
7. LONGITUDINAL BALANCE (@15HZ-50HZ) : 40dB MIN.
(@50HZ-600HZ) : 46dB MIN.
(@600HZ-3.4KHZ) : 52dB MIN.
8. DELAY DISTORTION (@200HZ-4KHZ) : 200uSEC MAX.
9. ATTENUATION (@32KHZ-1.1MHZ) : 45dB MIN.
10. ISOLATION (@T-R) : 1M OHM MIN.
(@T-G, R-G) : 10M OHM MIN.
11. LOOP CURRENT : 100mA
12. RoHS COMPLIANCE

						Atech® Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004		TITLE ADSL POTS SPLITTER	
								DWG. NO. CSA027005A	
	RELEASE	01/20/2006	RORY	SIMON	SUEDY	UNITS: M/M	SAFETY		SHEET 1 OF 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW <i>Pair</i>
REVISIONS						01/20/06			