









ELECTRICAL CHARACTERISTICS : <FOR 51130 COMPATIBLE>

- D.C.R. : PIN 4-1 = 0.268 OHM $\pm$ 12%
PIN 2-5 = 0.2 OHM $\pm$ 12%
PIN 6-9 = 7-10 = 0.723 OHM $\pm$ 12%
- INDUCTANCE (@10KHz, 0.1Vrms) : PIN 6-10 (<9-7 SHORT>) = 780uH $\pm$ 6%
- LEAKAGE INDUCTANCE (@100KHz, 0.1Vrms) :
PIN 6-10 (<W/H 7-9 2-4 1-5 SHORT>) = 20uH MAX.
- INTERWINDING CAP. (@100KHz, 0.1Vrms) :
PIN 6-5 (<W/H 7-9 2-4 SHORT>) = 30pF MAX.
- TURN RATIO (@15KHz, 0.1Vrms) :
PIN 6-10 (<9-7 SHORT>) : PIN 5-1 (<2-4 SHORT>) = 3.3 $\pm$ 1%
- HI-POT (@3000VAC, 1mA, 1SEC) : PIN 6-5 (<7-9 2-4 SHORT>)
- TRAY PACKING

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE ADSL TRANSFORMER	
								DWG. NO. ATS-555T	
	RELEASE	03/22/2005	PAIR	SUEDY	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>	
REVISIONS						03/22/05			