



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 2-4 = 1.39 OHM $\pm$ 12%
PIN 8-5 = 0.48 OHM $\pm$ 12%
PIN 7-6 = 0.39 OHM $\pm$ 12%
- INDUCTANCE (@10KHZ, 0.1Vrms) :
PIN 1-4 (2-3 SHORT) = 1.2mH $\pm$ 10%
- LEAKAGE INDUCTANCE (@100KHZ, 0.1Vrms) :
PIN 1-4 (2-3 5-7 6-8 SHORT) = 18uH MAX.
- INTERWINDING CAP. (@10KHZ, 0.1Vrms) :
PIN 1-8 (2-3 5-7 SHORT) = 66pF MAX.
- TURN RATIO (@750KHZ, 1Vrms) :
PIN 1-4 (2-3 SHORT) : PIN 8-6 (5-7 SHORT) = 2.79 $\pm$ 1%
- HI-POT (@1875VAC, 1mA, 1SEC) : PRI-SEC

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE TRANSFORMER	
								DWG. NO. ATS-565A	
	RELEASE	08/27/2002	DOLLY	JEFF	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>	
REVISIONS						08/27/02			