



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 2-4 = 8-6 = 7-5 = 1.11 OHM $\pm$ 12%
- INDUCTANCE (@10KHZ, 0.1Vrms) :
PIN 8-5 (W/H 6-7 SHORT) = 100uH $\pm$ 5%
- LEAKAGE INDUCTANCE (@300KHZ, 0.1Vrms) :
PIN 1-4 (W/H 2-3 8-6 7-5 SHORT) = 10uH MAX.
- INTERWINDING CAP. (@10KHZ, 0.1Vrms) :
PIN 1-8 (W/H 2-3 6-7 SHORT) = 30pF MAX.
- TURN RATIO (@1.32MHZ, 1Vrms) :
PIN 1-4 (2-3 SHORT) : PIN 8-5 (6-7 SHORT) = 1 $\pm$ 2%
- HI-POT (@1500VAC, 1mA, 1MIN) : PIN 1-8 (2-3 6-7 SHORT)

						Atech®		TITLE	TRANSFORMER
B	TURN RATIO	12/03/2002	PAIR	AL	SUEDY	Atech Technology Co. Ltd. TEL:0212794-6667 FAX:0212794-8014		DWG NO.	ATS-583
A	TURN RATIO	08/31/2002	DOLLY	AL	SUEDY				
	RELEASE	01/09/2002	DOLLY	CPLIU	SUEDY	UNITS:	SAFETY	SHEET 1 OF 1	
ND	DESCRIPTION	DATE	BY	CHK	APPD	M/M			
REVISIONS						DATE	01/09/02	DRAW	Pair