



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 791.8 Ω HM $\pm$ 12%
PIN 4-3 = 929.6 Ω HM $\pm$ 12%
- INDUCTANCE PARALLEL (@250HZ, 0.5Vrms) : PIN 1-2 = 30H MIN.
- INSERTION LOSS (@1KHZ, 1Vrms W/H 10K Ω HM) :
PIN 1-2 = 1.1dB $\pm$ 0.25dB
- FREQ. RESP. (@REF 1KHZ) : @300HZ = $\pm$ 0.3dB
@4KHZ = $\pm$ 0.3dB
- RETURN LOSS (@REF 10K Ω HM) : @300HZ = 20dB MIN.
@1KHZ = 20dB MIN.
@4KHZ = 20dB MIN.
- TURN RATIO (@6.4KHZ, 1Vrms) : PIN 1-2 : PIN 4-3 = 1 $\pm$ 1%
- HI-POT (@1250VAC, 1mA, 2SEC) : PIN 1-4

						Atech® Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004		TITLE 10K : 10K TRANSFORMER	
								DWG. NO. ATS-605	
	RELEASE	10/18/2002	DOLLY	KEVIN	SUEDY	UNITS: M/M		SAFETY	SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE 10/18/02			
REVISIONS						DRAW <i>Pair</i>			