



1. DCR : PIN 1-10 = 0.618 OHM MAX.
PIN 2-9 = 0.618 OHM MAX.
PIN 4-7 = 0.965 OHM MAX.
PIN 5-6 = 0.965 OHM MAX.
2. INDUCTANCE (@1KHZ, 0.1Vrms) :
PIN 1-10 = 48 uH ±8%.
PIN 2-9 = 48 uH ±8%.
PIN 4-7 = 100.8 uH +10% / -3%.
PIN 5-6 = 100.8 uH +10% / -3%.
3. CAPACITANCE (@1KHZ, 0.1Vrms) :
PIN 9-10 = 123 pF ±30%.
PIN 6-7 = 200 pF ±30%.
4. HI-POT (@0.5KVAC, 1mA, 2S) :
PIN 1-2, 4-5

C	L±8%	07/14 /2006	PAIR	MICHAEL	EUGENE	 Atech ® Atech Technology Co., Ltd. TEL:0212794-6667 FAX:0212794-8004	TITLE	TRANSFORMER
B	CAP= ±30%	06/09 /2006	PAIR	MICHAEL	EUGENE		DWG. NO.	
A	SCHEMATIC	01/13 /2006	BART	MICHAEL	SUEDY		ATS-721	
	RELEASE	11/23 /2004	BART	MICHAEL	SUEDY		UNITS:	SAFETY
NO.	DESCRIPTION	DATE	BY	CHK	APPD	M/M		SHEET 1 OF 1
REVISIONS						DATE	P/N:	DRAW
						11/23/04	CTA013001A	<i>Pair</i>