


ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 1.95 Ω HM MAX.
PIN 3-5 = 2.73 Ω HM MAX.
PIN 6-10 = 4.67 Ω HM MAX.
- INDUCTANCE (@1KHZ, 0.1Vrms) :
PIN 1-5 = 3.56 mH $\pm$ 5%.
PIN 6-10 = 3.56 mH $\pm$ 5%.
- INTERWINDING CAP. (@1KHZ, 0.1Vrms) :
PIN 1-10 = 123 pF MAX.
- TURN RATIO :
(@100KHZ, 1Vrms)
PIN 1-5:6-10 = 1 $\pm$ %.
(@100KHZ, 1Vrms)
PIN 1-3:3-5 = 1 $\pm$ 1%.
- HI-POT (@500VAC, 0.5mA, 2S) : PIN 1-6

						Atech®		TITLE
						Atech Technology Co. Ltd.		TRANSFORMER
						TEL:02794-6667 FAX:02794-8004		DWG. NO.
								ATS-731
RELEASE		01/07/2005	BART	MICHAEL	SUEDY	UNITS:	SAFETY	SHEET 1 OF 1
M/M								
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS						01/07/05	CTA013007A	Pair