








ELECTRICAL CHARACTERISTICS :

- 1.D.C.R. : PIN 1-3 = 2-4 = 8-6 = 7-5 = 1.11 OHM +/- 12%.
- 2.INDUCTANCE(@10K HZ , 0.1 Vrms) :
PIN 8-5 = 100 uH +/- 5% (W / H 6-7 SHORT)
- 3.LEAKAGE INDUCTANCE(@300K HZ , 0.1 Vrms) :
PIN 1-4 = 10 uH MAX.(W / H 2-3 8-6 7-5 SHORT)
- 4.INTERWINDING CAP. (@10K HZ , 0.1Vrms) :
PIN 1-8 = 30pF MAX.(W / H 2-3 6-7 SHORT)
- 5.TURN RATIO(@1.32M HZ , 1Vrms) :
PIN 1-4(2-3 SHORT) : PIN 8-5(6-7 SHORT) = 1 +/- 2%.
- 6.HI-POT(@1500 VAC , 1 mA , 1 MIN) :
PIN 1-8 (2-3 6-7 SHORT)

						Atech [®] Atech Technology Co., Ltd. TEL: (02)2794-6667 FAX: (02)2794-8004	TITLE TRANSFORMER
B	TURN RATIO	12/03 /2002	Dolly	AL	Suedy		DWG NO. ATS-583
A	TURN RATIO	08/31 /2002	Dolly	AL	Suedy		
	RELEASE	01/09 /2002	Dolly	CPLIU	Suedy	UNITS M/M	SHEET 1 / 1
NO.	DESCRIPTION	DATE	BY	CHK	APP	DATE 20080828	P/N CTA607001A
REVISIONS						DRAW Isaac	