



1. D.C.R. PIN 1-3 = 105 Ω M $\pm$ 10% PIN 4-6 = 105 Ω M $\pm$ 10%
2. INDUCTANCE (@ 250HZ, 0.5V_{rms}, PARALLEL) 1-3 = 3 H MIN.
3. IMPEDANCE (@ 1KHZ, 0dBm, 6-4 W/H 400 Ω M)
1-3 = 600 Ω M $\pm$ 3%
4. INSERTION LOSS = 2.3 dB MAX.
(@ 1KHZ, 0dBm, W/H 400 Ω M LOAD)
5. FREQ. RESP. (@ 300HZ TO 4KHZ, REF. 1KHZ) = $\pm$ 0.12dB
6. RETURN LOSS: @300HZ = 28dB MIN. @1KHZ = 35dB MIN.
@4KHZ = 35dB MIN.
7. TURN RATIO : 1-3:6-4 = 1 $\pm$ 1%
8. HI-POT = 1250 VAC, 1mA, 2SEC. (PRI.-SEC.)

C	GLUE	12/08/2005	BART	MICHAEL	SUEDY	 Atech Technology Co., Ltd. TEL:(02)2784-8867 FAX:(02)2784-8004		TITLE 600: 400 TRANSFORMER	
B	SPEC.	11/14/2005	BART	LYS	SUEDY			DWG. NO.	
A	ERASE 8013	11/10/2005	BART	AL	SUEDY			ATC-05-042	
	RELEASE	08/29/2005	BART	EEFLYS	SUEDY	UNITS:		SAFETY	
ND	DESCRIPTION	DATE	BY	CHK	APPD	M/M		SHEET 1 OF 1	
REVISIONS						DATE		DRAW	
						08/29/05		<i>Pair</i>	