




ELECTRICAL CHARACTERISTICS: (FOR V.90, MEET UL1950)

1. D.C.R. : PIN 1-2 = 170 OHM +/-12%. PIN 3-4 = 150 OHM +/-12%
2. INDUCTANCE (@1KHZ, 1Vrms LP) : PIN 1-2 = 2.3Hy MIN.
3. INSERTION LOSS (@ 1KHZ, 0dBm, PIN 3-4 W/H 287 OHM)
PIN 1-2 = 3.5 dB MAX.
4. FREQ. RESP.(REF. 1KHZ) : @200HZ-4KHZ = +/-0.1dB
5. RETURN LOSS (REF. 600 OHM) : @ 200HZ - 4KHZ = 23dB MIN.
6. TURNS RATIO : PIN 1-2 : PIN4-3 = 1+/-1%
7. LONGITUDINAL BAL. = 60dB MIN.(@200-4KHZ)
8. T.H.D. (@600HZ,-10dBm) = -80dB TYP.
9. HI-POT (@1650VAC, 1mA, 2SEC.) PRI. - SEC.

C	ADD P/N	06/28/2006	PAIR	EUGENE	Atech® Atech Technology Co., Ltd. TEL:(02)2794-6867 FAX:(02)2794-8004	TITLE	600 : 287 TRANSFORMER
B	pin 腳變更	05/28/00	PAIR	SUEDY		DWG. NO.	ATS-348AL
A	ADD TOLERANCE	05/15/00	RDY	SUEDY			
	RELEASE	11/26/99	PAIR	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
NO	DESCRIPTION	DATE	BY	CHK	APPD	P/N: CTP30800CA	DRAW Pair
REVISIONS					11/26/99		