



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 2.37 K Ω HM MAX.
PIN 4-3 = 2.82 K Ω HM MAX.
- INDUCTANCE PARALLEL (@250HZ, 0.5Vrms) : PIN 1-2 = 70H MIN.
- INSERTION LOSS (@1KHZ, 1Vrms, PIN 4-3 W/H 20K Ω HM) :
PIN 1-2 = 1.3dB $\pm$ 0.25dB
- FREQ. RESP. (@REF 1KHZ) : @300HZ = $\pm$ 0.3dB
@4KHZ = $\pm$ 0.3dB
- RETURN LOSS (@REF 20K Ω HM) : @300HZ = 18dB MIN.
@1KHZ = 18dB MIN.
@4KHZ = 18dB MIN.
- TURN RATIO (@12KHZ, 1Vrms) : PIN 1-2 : PIN 4-3 = 1 $\pm$ 1%
- HI-POT (@1250VAC, 1mA, 2SEC) : PIN 1-4

						Atech®		TITLE 20K : 20K TRANSFORMER
						Atech Technology Co. Ltd.		DWG. NO. ATS-667
						TEL: (02) 2794-6667 FAX: (02) 2794-8004		
RELEASE		08/06/2003	RORY	KEVIN	SUEDY	UNITS: M/M	SAFETY	SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N: CTP308036A	DRAW Pair
REVISIONS						08/06/03		