






ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-3 = 138 OHM MAX.
PIN 4-6 = 130 OHM MAX.
- INDUCTANCE PARALLEL (@250HZ, 0.5Vrms) : PIN 1-3 = 2.8H MIN.
- INSERTION LOSS (@1KHZ, 0dB) : 4-6 W/H 365 OHM LOAD = 2.8dB MAX.
- FREQ. RESP. (REF, 1KHZ) : (@300HZ) = ± 0.5 dB
(@4KHZ) = ± 0.5 dB
- RETURN LOSS (REF 600 OHM) : (@300HZ) = 25dB MIN.
(@1KHZ) = 30dB MIN.
(@4KHZ) = 30dB MIN.
- TURN RATIO (@20KHZ, 1Vrms) : PIN 1-3 : PIN 6-4 = $1 \pm 1\%$
- HI-POT (@1KVAC, 1mA, 2SEC) : PIN 1-6
- RoHS COMPLIANT

						Atech®		TITLE
						Atech Technology Co. Ltd.		TRANSFORMER
						TEL:022794-6667 FAX:022794-8004		DWG. NO.
						ATC-02-050R		
RELEASE		08/02/2006	pair	EUGENE	UNITS:	SAFETY		SHEET 1 OF 1
NO. DESCRIPTION		DATE	BY	CHK	APPD	P/N:		DRAW
REVISIONS						08/02/06		Pair
						CTP30803CA		