



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 2.37 KΩ MAX.
PIN 4-3 = 2.82 KΩ MAX.
- INDUCTANCE PARALLEL (@250HZ, 0.5Vrms) : PIN 1-2 = 70H MIN.
- INSERTION LOSS (@1KHZ, 1Vrms, PIN 4-3 W/H 20KΩ) :
PIN 1-2 = 1.3dB ± 0.25dB
- FREQ. RESP. (@REF 1KHZ) : @300HZ = ±0.3dB
@4KHZ = ±0.3dB
- RETURN LOSS (@REF 20KΩ) : @300HZ = 18dB MIN.
@1KHZ = 18dB MIN.
@4KHZ = 18dB MIN.
- TURN RATIO (@12KHZ, 1Vrms) : PIN 1-2 : PIN 4-3 = 1 ± 1%
- HI-POT (@1250VAC, 1mA, 2SEC) : PIN 1-4
- RoHS COMPLIANT

						Atech®		TITLE 20K : 20K TRANSFORMER
						Atech Technology Co. Ltd.		DWG. NO. ATS-667R
						UNITS: M/M		SHEET 1 OF 1
						DATE 04/22/08		DRAW Pair
REVISIONS						P/N: CTP30803NA		
NO.	DESCRIPTION	DATE	BY	CHK	APPD			
	RELEASE	04/22/2008	Pair	Vincent	Eugene			