

PK-K6
DS-001

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING			
		ATS-122													
BOBBIN: BB-EE1605-11														BOTTOM VIEW PIN LOCATION	
CORE: LM-EE16-02															
GAP:															
TAPE: 3M#1350W															
ASSEMBLY: 1*1 共 24 PAIRS 外色 5.5 mm TAPE 2 Ts															
FRAME (CLIP): CAN: CN-S1818-02															
PIN#1 INDICATOR: 上方白点 (印在 LABEL 上)															
TAP WID mm	TAP LVR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL				
10.5	3	W1	1	3	顺	0.07	2 UEN	980	厚	密	Y				
10.5	2	W2	6	4	逆	0.08	3 UEN	980	薄	疏					
		W3													
		W4													
		W5													
		W6													
		W7													
												REMARKS			
												1. 绕 W1 的 BOBBIN PIN#1 朝外, 绕 W2 的 BOBBIN 反插 PIN#1 朝内。 2. SIDEWALL 贴法 查看 ATS-122 标准制程。 3. 成品加 CAN 灌 EPOXY。			
												PAGE / OF / REV. D			

REMARK: 4. SIDEWALL 为 11 mm * 11 mm, 2 层 3M#1350