

CUSTOMER		PART NUMBER	REV	CONSTRUCTION										SCHEMATIC DRAWING		
客		ATS-418B														
BOBBIN: UI-11.7, 8/8 PINS														BOTTOM VIEW PIN LOCATION		
CORE: CORE, UI-11.7, NC-2H																
GAP: 兩邊各用 1/2 mile HOMEX																
TAPE: PPI H 70/100																
ASSEMBLY: CORE 組合後, 先用治具固定, 再用 GL-014 固定, 再用 CORE 固定																
FRAME (CLIP):																
PIN#1 INDICATOR: 黑印在 LABEL 上																
TAP WID mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL					
		W1	6	7	順	0.04	1	VIEW	1800							
		W2	4	3	順	0.1	2	VIEW	11							
		W3	3	2	順	0.2	2	VIEW	11							
		W4	5	1	順	0.1	2	VIEW	3							
		W5														
		W6														
		W7														
REMARKS												1. 繞 W1~W7 時, BOBBIN PIN#1 朝外. 2. SEC#2 繞 300TS SEC#3 繞 300TS+ SEC#4 繞 300TS- SEC#5 繞 300TS+ SEC#6 繞 300TS- SEC#7 繞 300TS 3. PIN#6 與 PIN#7 繞線繞法 並繞在 DUMMY PIN 上				
PAGE 1 OF 1												REV. A				

REMARK 4: W5~W7 繞在 SEC#2

REMARK 5: 插入 I 片時, 先在 BOBBIN 內夾少許 GL-016, 不可太多, 否則膠會擠出.

REMARK 6: 包外層 TAPE 時, 先包一圈, 貼上 LABEL 再貼半圈, 繞尾在側面.

REMARK 7: 夾 GL-014 時, 3 夾要夾在 PIN#1 的那一端, 並和 BOBBIN 固定在一起, 另外兩夾夾在 PIN#7 的那一端, 夾膠時不能沾到 BOBBIN 上, 只要夾 E 和 I core 就可.