

CUSTOMER		PART NUMBER		REV	CONSTRUCTION										SCHEMATIC DRAWING		
ASKEY		ATS-423															
BOBBIN:																	
BB-EP13-01																	
CORE:																	
FC-EP13-12																	
GAP:																	
ORIGINAL																	
TAPE: PPI#70/100																	
3M#1350W																	
ASSEMBLY: CORE組合時, 鏡面要																	
乾淨有GAP印在PIN#1端, 外徑8mm																	
FRAME(CLIP): KAPTON TAPE 2TS,																	
並在BOBBIN與CORE內側四角裝VAR-005固定																	
PIN#1 INDICATOR:																	
黑英印在 LABEL 上																	
TAP WID mm	TAP LVR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL						
雙線	線	W1	1	3	順	0.16	ZUEW	30		來回繞線							
3M#1350W 8mm	I	W2	2	4	順	0.16	ZUEW	30		來回繞線							
雙線	線	W3	10	8	反	0.2	TEX-E	30		密							
		W4	9	7	反	0.2	TEX-E	30		密							
		W5															
		W6															
		W7															
REMARKS																	
1. 繞W1, W2時, BOBBIN PIN1朝外。																	
2. 繞W3, W4時, BOBBIN 反梯 PIN1朝內。																	
3. W1與W2 須同軸分繞, W3與W4 須同軸分繞。																	
4. CORE外包8mm TAPE, 先包1T, 貼上LABEL後, 再包1T, 並在TAPE結尾部分刷封膠VAR-005固定之。																	
PAGE 1 OF 1												REV. A					