

CUSTOMER		PART NUMBER		REV		CONSTRUCTION								SCHEMATIC DRAWING			
ASKEY		ATS-424F															
BOBBIN: BB-EP13-10																BOTTOM VIEW PIN LOCATION	
CORE: FC-EP13-30																	
GAP: ORIGINAL																	
TAPE: 3M#56 Super#10 PPI#70/00																	
ASSEMBLY: CORE組合時, 鏡面保持 乾淨, 有GAP的在PIN#7側, 外包PPI#70/00																	
FRAME(CLIP): 7.9mm 2Ts																	
PIN#1 INDICATOR: DOT																	
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL						
3M#56 7.9mm	2	W1	10	8	反	0.12	2	NEW	50	super#10 2mm 1T 在兩側	密						
3M#56 7.9mm	2	W2	1	3	順	0.12	2	NEW	50	super#10 2mm 2Ts 在兩側	密						
3M#56 7.9mm	2	W3	9	7	反	0.12	2	NEW	50	super#10 2mm 1T 在兩側	密						
3M#56 7.9mm	2	W4	2	4	順	0.12	2	NEW	50	super#10 2mm 2Ts 在兩側	密						
3M#56 7.9mm	2	W5															
		W6															
		W7															
		W8															
												REMARKS					
												1. 繞W1前先用3M#56 7.9mm 打底1T, 須重疊2mm 2. 繞W1, W3 BOBBIN PIN#1 朝內 3. 繞W2, W4 BOBBIN PIN#1 朝外 4. 成品須裝6支GL-014 烤乾固定					
												PAGE 1 OF 1					
												REV. A					
												Design Engineer: Michael					