

CUSTOMER		PART NUMBER		REV	CONSTRUCTION										SCHEMATIC DRAWING	
GVC		ATS-440														
BOBBIN: BB-EP13-06																
CORE: CORE: EP13, 1500H, (70KIN), AL: 280H ± 3% (0.1KHZ, 7mVrms, 200mADC) AL: 205H (1W)																
GAP: ORIGINAL																
TAPE: 3MH 1350W																
ASSEMBLY: CORE 組合時, 鏡面要乾透, 有GAP的自PIN#1端, 外面8mm TAPE															BOTTOM VIEW PIN LOCATION	
FRAME (CLIP): 2Ts, 並自BOBBIN 每CORE內刻文要寫G1-014膠固定																
PIN#1 INDICATOR: (黑, 要印在 LABEL V) 缺口															REMARKS 1. 繞W1時, BOBBIN PIN#1 朝外 2. 繞W2時, BOBBIN 反插 PIN#1 朝內 3. CORE 須先放正, 再要膠 固定。	
TAP WID mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL					
8	1	W1	4	1	反	0.12	2 VIEW	73		來回 上繞						
8	2	W2	10	7	反	AVG #32	TEX-E	51		空						
		W3														
		W4														
		W5														
		W6														
		W7														
PAGE 1 OF 1												REV.				