

CUSTOMER			PART NUMBER		REV	CONSTRUCTION												SCHEMATIC DRAWING						
矽晶行			ATC-01-030B		A																			
BOBBIN: UI-11.7, 8/8 PWS, SMD, 7 SEC																								
BB-UI/2-01 (H-050-1.5)																								
CORE: UI-11.7, 3090, Frame 12																								
FC-UI/2-02																								
GAP: 6 miles NoTex Paper 在兩面																								
TAPE: NAN YA, BD21																								
ASSEMBLY: CORE 組合時, 於兩面各放																								
-J 2mm x 5mm 6 miles NoTex																								
FRAME(CLIP): Paper, 製具固定後再																								
夾二直線 GL-04 膠 烘乾固定.																								
PIN#1 INDICATOR:																								
TAP WID Mm	TAP LYR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL													
15.9 mm	2	W1	6	1	順	0.03	1 UZW	2/50																
		W2	4	1	順	0.3	2 UZW	16	X															
		W3																						
		W4																						
		W5																						
		W6																						
		W7																						
		W8																						
REMARK 5. CORE 組合前 於 BOBBIN 中 CORE 靠 PIN 兩側 夾二直線 GL-04 膠 烘乾固定														PAGE 1 OF 1		REV. B								
REMARK 6. 包 TAPE 時須保持 TAPE 的平整性														Design Engineer: Shiah										

REMARK 5. CORE 組合前 於 BOBBIN 中 CORE 靠 PIN 兩側 夾二直線 GL-04 膠 烘乾固定

REMARK 6. 包 TAPE 時須保持 TAPE 的平整性

