

CUSTOMER	PART NUMBER	REV	CONSTRUCTION												SCHEMATIC DRAWING	
碩晶行	ATC-02-055															
BOBBIN: BB-U010-01 2 SECTION, 4/4 PINS (盈勤 U1201)															BOTTOM VIEW PIN LOCATION	
CORE: FC-U010-02 A07. AL=1300 +/- 25% (越峰)																
GAP: ORIGINAL																
TAPE: 3M#1350																
ASSEMBLY: core 組合後, 固定在 PIN 1. PIN 4 側, 外加 clip																
FRAME(CLIP): FM-U010-01 (申盛 U09.8)																
PIN#1 INDICATOR: (CN-S1716-01) 白美印在 CAN 上																
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRF PAG	DEN LSN	SIDE WALL					
3M#1350 3mm	2TS	W1	2	1	順	0.13	10EW	277		密						
3M#1350 3mm	2TS	W2	3	4	反	0.13	10EW	277		密						
		W3														
		W4														
		W5														
		W6														
		W7														
		W8										REMARKS 1. 繞 W1 時 PIN2 朝外 2. 繞 W2 時 PIN2 朝內 3. 放入 CAN 灌膠時需 校正 4. 膠不可灌太滿, 而 CAN 邊緣切齊即可				
PAGE OF REV. Design Engineer: Kevin A																