

03-233

ATECH TECHNOLOGY CO., LTD.

DESIGN SHEET

DS-001

CUSTOMER	PART NUMBER	REV	CONSTRUCTION													SCHEMATIC DRAWING					
靖承	ATC-03-030B																				
BOBBIN: 用BB-E21604-01 掃上 P2W#3. 10/10PWS																BOTTOM VIEW PIN LOCATION					
CORE: 用PC-EE1605-08 度AL=75uH±3%																					
GAP: ORIGINAL																REMARKS					
TAPE: 3M#56																					
ASSEMBLY: Core 組合時, 有GAP 的在上方, 外包3M#56 4mm 2Ts																					
FRAME(CLIP):																					
PIN#1 INDICATOR: DOT																					
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL										
		W1	1	3	順	0.23	2UEW	60		密											
8.5	1	W2	2	1	順	0.23	2UEW	10		均緩層 拉直角											
8.5	3	W3	6	10	順	0.4	TEX-E	4		緩層 拉直角											
	三線	W4	6	10	順	0.4	TEX-E	4		"											
		W5	6	10	順	0.4	TEX-E	4		"											
		W6	7	9	順	0.23	2UEW	10		均緩層 拉直角											
8.5	3	W7	3	4	順	0.23	2UEW	60		密											
8.5	2	W8																			
												PAGE OF REV.									
												Design Engineer:									
												Kavin									

2 成品需校正含浸, Core 組合時需由上向下靠緊.

3. 三層絕緣線結尾時需剥皮.