

CUSTOMER			PART NUMBER		REV	CONSTRUCTION										SCHEMATIC DRAWING	
ATC-03-044			A														
BOBBIN: BB-EE1605-07																	
CORE: FC-EF1605-01																	
GAP:																	
TAPE: 3M#1350, 10.5mm																	
ASSEMBLY: 組合時, 用 3M#1350 4mm 2Ts, 真膠 (GL-014) 兩面烤乾!															BOTTOM VIEW PIN LOCATION		
FRAME(CLIP):																	
PIN#1 INDICATOR: V 字 DOT																	
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL						
3M#1350	2	W1	3	1	順	0.32	2UEW	65		密							
10.5mm	2	W2	6	4	順	0.07	2UEW	1K		密							
3M#1350	2	W3															
10.5mm		W4															
		W5															
		W6															
		W7															
		W8											PAGE 1 OF 1 Design Engineer: Kevin REV. A				

REMARKS

1. 繞 W₁ 時, PIN#1 朝外
 2. 繞 W₂ 時, PIN#1 朝內
 3. 成品須真膠 (GL-014)
 烤乾後, 再放正
 合浸。