

CUSTOMER		PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING	
碩 碩		ATC-04-056B															
BOBBIN: BB-U10-03																	
CORE: FC-U109-04																	
GAP: 聚酯亞胺膠帶裁切 5x1.7mm 貼在I core兩端																	
TAPE: TP-KT019-02																	
ASSEMBLY: 組裝後需以鐵夾固定鉄 芯烤乾固定																	
FRAME(CLIP):																BOTTOM VIEW PIN LOCATION	
PIN#1 INDICATOR:																	
TAP WID Min	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL			REMARKS			
		W1	5	6	順	0.03	P180 G2	2500		密							
		W2	4	1	順	0.29	2UEW	20		密							
18.8	1.5T	W3															
		W4															
		W5															
		W6															
		W7															
		W8										PAGE 1 OF 1		REV. B			
Design Engineer: yaker																	

REMARKS: 5. CORE 組裝後於 Bobbin 每 Core 接合處夾一條 GL-014, U-Core 每 1-Bar 接合處夾一條 GL-014.

6. TAPE 1.5T 貼尾於 1-8 pin, 開始於 5-6 pin, 結束缺口朝向底部.