

05-35

ATECH TECHNOLOGY CO., LTD.

DESIGN SHEET

DS-001

CUSTOMER		PART NUMBER		REV		CONSTRUCTION							SCHEMATIC DRAWING	
MIKROTIKLS		ATC-04-078												
BOBBIN: BB-EFD20-04														
CORE: HC-EFD20-06														
GAP: 單面貼3M#74, 1層														
TAPE: 3M#56 PPI#70100														
ASSEMBLY:													BOTTOM VIEW PIN LOCATION	
FRAME(CLIP): 外包 PPI#70100 6mm 2Ts.														
PIN#1 INDICATOR: 凹角(黑點印在LABEL上)														
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS 1. 繞 W1, W2, W5, W6, W7 時 BOBIN PIN1 腳朝外 2. 繞 W3, W4 時 BOBIN PIN1 朝內 3. W1, W2 繞完須留適當長度待繞完 W3, W4 後使用原線材繞 W5, W6 4. W1, W2, W3, W4 為雙線起繞 共4線並繞		
		W1	1	A1	反	0.25 X2	1uew 本	9.5		密				
交叉		W2	3	A2	反	0.25 X2	1uew 紅	9.5		密				
14mm 3M#56	1	W3	6	7	順	0.35 X2	1uew 本	7		密				
交叉		W4	8	9	順	0.35 X2	1uew 紅	7		密				
14mm 3M#56	1	W5	A1	2	反	0.25 X2	1uew 本	9.5		密				
交叉		W6	A2	4	反	0.25 X2	1uew 紅	9.5		密				
14mm 3M#56	1	W7	3	5	反	0.12 X2	1uew 本	4		均去 均回				
14mm 3M#56	>	W8										PAGE 1 OF 1	REV. B	

REMARKS: 5. 成品須索 2 桌 GL-014 烤乾後再含浸.

6. W3, W4 需拉直回