

CUSTOMER			PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING						
麗臺科技			ATC-04-079																				
BOBBIN: BB-UI10-02																							
CORE: FC-UI09-05																							
GAP: 聚醯亞胺膠帶裁切 5*1.7mm 貼在 I core 兩端																							
TAPE: TP-KT019-02																							
ASSEMBLY: 以鉄夾固定桌膠烤乾																	BOTTOM VIEW PIN LOCATION						
FRAME(CLIP):																							
PIN#1 INDICATOR:																	REMARKS						
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ											COA	TUR	CRE PAG	DEN LSN	SIDE WALL		
		W1	6	7	順	0.045											2UEW	1300		密			
		W2	5	1	順	0.21											2UEW	3		密			
		W3	4	3	順	0.21											2UEW	13		密			
		W4	3	2	順	0.21											2UEW	13		密			
		W5																					
		W6																					
		W7																					
		W8																					
雙線 18.8 1.5T												PAGE 1 / OF 1 Design Engineer: <i>yaker</i>		REV. <i>C</i>									

REMARKS: 6. TAPE 1.5T 結尾於 1-9 pin, 開始於 6-7 pin, 結束缺口朝向底部。

7. W3 與 W4 雙線併繞, 需先繞 W3。