

CUSTOMER		PART NUMBER		REV		CONSTRUCTION								SCHEMATIC DRAWING	
		ATPL-068A		A											
BOBBIN:														CAN CN-S1010-002	
CORE:														TR-004/02-03	
GAP:															
TAPE:															
ASSEMBLY:								BOTTOM VIEW PIN LOCATION							
FRAME(CLIP):															
PIN#1 INDICATOR:						上方圖突									
TAP WID mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL				
		W1	1	4	順	AUG 38	DOA 01944 -1.5	9 1/2		±0.1					
		W2	8	5	:	0.15	2 NEW	2 1/2		=					
		W3													
		W4													
		W5													
		W6													
		W7													
												REMARKS			
												1. W1繞線線內圈10TS, 外圈9TS. 2. W2繞線線內圈6TS, 外圈5TS. 3. 美膠時底部以磁鐵 固定core,防止core浮高. 4. 須確認 core完全置於 CAN內,讓接腳可完全平貼 於一平面. (GL-019) 5. 成品須灌膠將core固定			
												PAGE 1 OF 1			
												REV. D			

REMARK: 6. 繞線要平整, 成品限高 2.3mm MAX.