

CUSTOMER		PART NUMBER		REV		CONSTRUCTION						SCHEMATIC DRAWING	
ASKEY		ATS-424B											
BOBBIN: BB-EP13-10													
CORE: FIC-EP13-30													
GAP: ORIGINAL													
TAPE: 3M#74, 3M#Super10 PPI #70/100													
ASSEMBLY: CORE組合時、鏡面要乾淨 有GAP則在PIN#1端、組合後、外包						BOTTOM VIEW PIN LOCATION							
FRAME(CLIP): PPI #70/100, 8mm TAPE 2TS 並在線尾用少許VAROOS固定													
PIN#1 INDICATOR: 黑點印在LABEL上													
TAP WID Mm	TAP LVR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS	
3M#74 7.9mm	2	W1	9	7	順	Q14	1	UEW	50	3M#Super10 1.4mm各2TS 在兩端二層		1.線W1時, BOBBIN PIN#1朝內	
		W2										2.線W2, W4時, BOBBIN 反轉, BOBBIN PIN#1朝外.	
		W3	1	3	反	Q14	1	UEW	50	3M#Super10 1.4mm各4TS 在兩端四層		3.線W5時, BOBBIN 反轉, BOBBIN PIN#1朝內	
雙結		W4	2	4	反	Q14	1	UEW	50			4. W2, W4線同軸分結	
3M#74 7.9mm	2	W5	10	8	順	Q14	1	UEW	50	3M#Super10 1.4mm各2TS 在兩端二層		5.線W前, 先貼3M#74, 7.9mm TAPE 1T, 重疊須>mm min.	
3M#74 7.9mm	2	W6										6.成品須求GL-014 6夾烤乾固足.	
		W7										7.CREEPAGE用 3M#Super10, 1.4mm±0.1	
		W8											
PAGE 1 OF 1												REV.	