

CUSTOMER	PART NUMBER	REV	CONSTRUCTION											SCHEMATIC DRAWING	
TODOS	ATS-467														
BOBBIN: BOBBIN, POT 18/11, 8/8 PINS.															
CORE: CORE, PP-18/11, NC-14 AL=74.5NH±13%															
GAP: ORIGINAL															
TAPE:															
ASSEMBLY: CORE組合時, 有GAP在PIN端, 組合後, 用VAR-001刷膠並固之。														BOTTOM VIEW PIN LOCATION	
FRAME(CLIP):															
PIN#1 INDICATOR: 缺角															
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS 1. 繞W1~W4時, BOBBIN PIN與內 2. 繞線要平整, 不可分叉 3. 繞線纏膠後須整線 4. CORE組合時, 先將上方圓 CORE內側刷一層膠, 並在 中心插一支電木棒, 再放入 線包, 最後在另一core兩側 刷一層薄膠(不可過多), 組 合後將線包放正, 並用治 具夾緊固定。			
		W1	1	2	順	0.14	2	UEW	73						
XX 繞		W2	3	4	=	0.14	2	UEW	73						
		W3	5	6	=	AWG #34	TEFZEL 藍菱	44							
XX 繞		W4	6	7	=	AWG #34	TEFZEL 藍菱	44							
		W5													
		W6													
		W7													
		W8													
PAGE 1 OF 1												REV.			