

CUSTOMER		PART NUMBER		REV	CONSTRUCTION										SCHEMATIC DRAWING	
CARINDA		ATS-553														
BOBBIN:																
CORE: CORE, EPT. NC-2H1																
AL=1000uH ±5%																
GAP:																
TAPE:																
ASSEMBLY: CORE組合後、外加FRAME						BOTTOM VIEW PIN LOCATION										
FRAME(CLIP):																
PIN#1 INDICATOR:																
TAP WID Mm	TAP LVR	WID	STR	END	CW/CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS				
4	2	W1	1	2	順	0.13	NEW	15		均繞在直徑		1. 繞W1時, BOBBIN PIN#1朝外. 2. 繞W2, W3時, BOBBIN反掉, PIN#1朝內. 3. 繞W4時, BOBBIN反掉, PIN#1朝外. 4. 成品要6支GL-014烤乾固定. 5. 繞線要平整, 否則會胖.				
4	2	W2	5	6	順	0.13	NEW	41		均繞在直徑						
4	2	W3	4	5	順	0.13	NEW	41		均繞在直徑						
4	2	W4	2	3	順	0.13	NEW	15		均繞在直徑						
4	2	W5														
		W6														
		W7														
		W8														
PAGE / OF / REV.																