

CUSTOMER		PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING			
丑元		ATS-626A																	
BOBBIN: BB-EP13-09																		BOTTOM VIEW PIN LOCATION	
CORE: NC-2H AL-62nH±3%																			
GAP:																			
TAPE: 3M#1350W, PPI#70100																			
ASSEMBLY: 組合時, 有GAP的在PIN#1 外包 7.9mm PPI#70100 TAPE FRAME (CLIP): ≥ Ts, 並在 BOBBIN 有 CORE 交接處夾 6 夾 GL-014 烤乾 PIN#1 INDICATOR: 固定 斜角 (黑點印在 LABEL 上)																			
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL	REMARKS 1. 繞 W1 時, PIN#1 朝外 2. 繞 W2 時, PIN#1 朝內 3. 夾膠時, CORE 由 PIN#1 側向內推, 烤乾固定							
3M#1350W 3.5mm	2	W1	1	5	順	0.11	2050V	284		密									
3M#1350W 3.5mm	2	W2	6	10	反	0.11	2050V	284		密									
		W3																	
		W4																	
		W5																	
		W6																	
		W7																	
		W8																	
PAGE / OF / REV.												Design Engineer:							