

02-183

CUSTOMER	PART NUMBER	REV	CONSTRUCTION											SCHEMATIC DRAWING	
台林通訊	ATS-629														
BOBBIN: EPX7 .1 SEC 8/8 PINS 品翔 S-709 PIN 內彎														BOTTOM VIEW PIN LOCATION	
CORE: EpX7 3E55 AL=387mH±6%															
GAP: ORIGINAL															
TAPE: PPI #70100															
ASSEMBLY: CORE 組合時, 鐵面要乾淨. 有GAP在PIN 1端, 組合後外包 PPI #70100															
FRAME(CLIP): 7mm TAPE 2TS 結尾用少 許 VAB-008 固定															
PIN#1 INDICATOR: 黑尖印在 LABEL 上															
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WTR SIZE	COA	TUR	CRE PAG	DEF LSN	SIDE WALL				
		W1	8	5	反	0.13	2UEW	23		密					
		W2	1	3	順	0.13	FWX-E	22		密					
		W3	2	4	順	0.13	FWX-E	22		密					
		W4	7	6	反	0.14	2UEW	23		密					
		W5													
		W6													
		W7													
		W8										REMARKS 1. 繞 W1 時, BOBBIN PIN 1 朝內 2. 繞 W2, W3 時, BOBBIN 反插, PIN 1 朝外 3. 繞 W4 時, BOBBIN 反插, PIN 1 朝內 4. 繞線要平整 否則會胖 5. 成品需夾 GL-104 螺絲固定			
PAGE 1 OF 1											REV.				
Design Engineer:											Kevin				