

02-708

ATECH TECHNOLOGY CO., LTD.

DESIGN SHEET

DS-001

CUSTOMER		PART NUMBER		REV		CONSTRUCTION										SCHEMATIC DRAWING	
光寬/突破		ATS-634															
BOBBIN: EP13 16/16 PWS SMD 品類 S-1315 (須商標)																	
CORE: CORE EP-13 NC-10H AL=76uH±3%																	
GAP: ORIGINAL																	
TAPE: Super#10 3M#74 PPI#70/00																	
ASSEMBLY: CORE 組合時, 有6點在PIN#9 側, 外包 PPI#70/00 2.5mm 2Ts																	
FRAME(CLIP):																BOTTOM VIEW PIN LOCATION	
PIN#1 INDICATOR: 黑點印在 LABEL 上																	
TAP WID Mm	TAP LYR	WID	STR	END	CW/ CCW	WIR SIZ	COA	TUR	CRE PAG	DEN LSN	SIDE WALL						
雙	線	W1	1	3	順	0.15	2UEW 本	12		密							
		W2	2	4	順	0.15	2UEW 紅	12		密							
雙	線	W3	5	7	順	0.15	2UEW 本	24		密							
		W4	6	8	順	0.15	2UEW 紅	24		密							
3M#74 7.9mm	2	W5	9	11	反	0.16	2UEW 本	48	3M#10 1.4mm 4Ts 在兩側	密							
雙	線	W6	14	16	反	0.16	2UEW 紅	48		密							
3M#74 7.9mm	2	W7	1	3	順	0.17	2UEW 本	12	3M#10 1.4mm 4Ts 在兩側	密							
雙	線	W8	2	4	順	0.17	2UEW 紅	12		密							
雙	線	W9	5	7	順	0.17	2UEW 本	24		密							
		W10	6	8	順	0.17	2UEW 紅	24		密							
3M#74 7.9mm	2											REMARKS					
												1. 繞 W1, W2, W3, W4, W5, W6, W7, W8, W9, W10 BOBBIN PIN#1 朝外 2. 繞 W5, W6 BOBBIN PIN#1 朝內 3. 成品需夾 6 點 GL-04 烤乾固定。 4. 繞線多尾時, 需拉直角錐腳 5. PIN 10, 12, 13, 15 剪掉					
PAGE 1 OF 1										REV.							
Design Engineer: Kevin																	